

DS-7204/7208/7216HFI-ST/SE Standalone DVR




DS-7208/7216HFI-ST/SE



DS-7204HFI-ST/SE

Key Features

- H.264 video compression
- Up to 4CIF resolution recording
- VGA output at 1280 × 1024 resolution
- Dual-stream
- 4/8/16-ch synchronous playback
- SADP(IP Finder), NTP, DHCP,SMTP protocols



Rear Panel of DS-7216HFI-ST/SE



- | | |
|------------------------|----------------------------------|
| 1. USB Interface | 6. LAN |
| 2. Video out | 7. RS-485 interface |
| 3. Video in | 8. 12 VDC power supply interface |
| 4. Audio in, audio out | 9. Power switch |
| 5. VGA interface | 10. GND |

Specifications

	DS-7204HFI-ST/SE	DS-7208HFI-ST/SE	DS-7216HFI-ST/SE
Video/Audio input			
Video compression	H.264		
Analog video input	4-ch	8-ch	16-ch
Video interface	BNC connector (1.0 Vp-p, 75 Ω); PAL / NTSC self-adaptive		
Audio compression	G.711		
Audio input	1-ch, RCA connector (2.0 Vp-p, 1 kΩ)		
Voice talk input	1-ch, RCA (2.0 Vp-p, 1 kΩ)		
Video/Audio output			
Recording resolution	4CIF / 2CIF / CIF		
VGA output	1-ch, resolution: 1280 × 1024 /60 Hz, 1024 × 768 /60 Hz		
CVBS output	1-ch, BNC connector (1.0 Vp-p, 75 Ω); Resolution: PAL: 704 × 576, NTSC: 704 × 480		
Audio output	1-ch, RCA connector (linear, 1 kΩ)		
Frame rate	25 fps (P) / 30 fps (N)		
Video bit rate	32 kbps ~ 2048 kbps, or user defined (max. 3072 kbps)		
Stream type	Video, Video & Audio		
Audio bit rate	64 kbps		
Dual-stream	Support (sub stream at CIF / QCIF)		
Synchronous playback	4-ch	8-ch	16-ch
Hard disk			
SATA	1 SATA interface	2 SATA interfaces	2 SATA interfaces
Capacity	Up to 2TB capacity for each disk		
External interface			
Network interface	1, RJ45 10M / 100M self-adaptive ethernet interface		
Serial interface	1 RS-485 full-duplex interface		
USB interface	2, USB 2.0		
General			
Power supply	12 VDC		
Consumption	≤ 10W (without hard disk or DVD-R/W)	≤ 10W (without hard disk or DVD-R/W)	≤ 15W (without hard disk or DVD-R/W)
Working temperature	-10 °C ~ +55 °C		
Working humidity	10% ~ 90%		
Chassis	Stand-alone 1U chassis	19-inch rack-mounted 1U chassis	19-inch rack-mounted 1U chassis
Dimensions (W x D x H)	315 × 230 × 45 mm	445 × 290 × 45 mm	445 × 290 × 45 mm
Weight	≤ 2kg (without hard disk or DVD-R/W)	≤ 4kg (without hard disk or DVD-R/W)	≤ 4kg (without hard disk or DVD-R/W)