

# CONVENTIONAL SYSTEM ACCESSORIES

## AD- 101 MANUAL CALL POINT (MS)

The Manual Call Point is tough, durable & highly visible. Alarm LED/s is provided inside the Call Point to indicate the Alarm condition.

### FEATURES

- ▶ Available for flush or Surface Mounting.
- ▶ Suitable for majority of conventional Fire Alarm System.

### SPECIFICATION

Voltage	18 -26 V.D.C.
Alarm Current	30 mA
Weight	540 gm
Dimension (mm)	115 x 90 x52
Colour	Red
Material of Cons.	MS



## AD- 501 SOUNDER (MS)

The Electronic sounder is designed for use within fire alarm systems, security systems and industrial signaling systems. It provides an audio warning which is suitable for place which needs audio indication.

### FEATURES

- ▶ 24 / 12 Volt DC operation
- ▶ High sound output with low current consumption.

### SPECIFICATION

Voltage	20 -26 V.D.C.
Alarm Current	180 mA
Weight	565 gm
Dimension (mm)	185 x 125 x 75
Colour	Red
Material of Cons.	MS



## AD -110 MRU / AD -110 MAU MANUAL RELEASE UNIT / MANUAL ABORT UNIT

### FEATURES

- ▶ ABS Plastic Body
- ▶ Front Protection Glass Cover
- ▶ Unbreakable Glass
- ▶ No /NC Potential Free Contacts

### SPECIFICATION

Voltage	18 -26 V.D.C.
Alarm Current	30 mA
Weight	140 gm
Dimension (mm)	85 x 85 x 50
Colour	Green
Material of Cons.	FR Polymer



## AD- 110 / AD - 110 BL (BLINKING TYPE) MANUAL CALL POINT (ABS)

The Manual Call Point is tough, durable & highly visible. Alarm LED is provided inside the Call Point to indicate the Alarm condition.

### FEATURES

- ▶ Available for flush or Surface Mounting.
- ▶ Suitable for majority of conventional Fire Alarm System.
- ▶ Front protection glass cover
- ▶ Unbreakable glass ABS plastic body

### SPECIFICATION

Voltage	18 -26 V.D.C.
Alarm Current	30 mA
Weight	140 gm
Dimension (mm)	85 x 85 x 50
Colour	Red
Material of Cons.	FR Polymer



AD-110



AD-110 BL

## AD- 502 SOUNDER ABS

The Electronic sounder is designed for use within fire alarm systems, security systems and industrial signaling systems. It provides an audio warning which is suitable for place which needs audio indication.

### FEATURES

- ▶ 24 / 12 Volt DC operation
- ▶ High sound output with low current consumption.

### SPECIFICATION

Voltage	20 -26 V.D.C.
Alarm Current	180 mA
Weight	370 gm
Dimension (mm)	115 x 115 x 75
Colour	Red
Material of Cons.	FR Polymer



## AD -110 EDR EMERGENCY DOOR RELEASE

### FEATURES

- ▶ ABS Plastic Body
- ▶ Front Protection Glass Cover
- ▶ Unbreakable Glass
- ▶ No /NC Potential Free Contacts

### SPECIFICATION

Voltage	18 -26 V.D.C.
Rated Current	3 Amp.
Weight	140 gm
Dimension (mm)	85 x 85 x 50
Colour	Green
Material of Cons.	FR Polymer

